

SciCan STATIM® G4

Cassette Autoclaves



STERILIZATION AND DRYNESS

at speeds faster than conventional chambered autoclaves



Fast Cycle Times

STATIM 2000 G4 unwrapped cycle times are the world's fastest at 6 minutes. Wrapped cycles, including drying, can be completed in as little as 35 minutes.

STATIM 5000 G4 can complete unwrapped cycles in as little as 9 minutes. Wrapped cycles, including drying, can be completed in as little as 40 minutes.



Reliable

For over 25 years, STATIM's unmatched speed, reliability, and dependability have made it one of the world's best selling cassette autoclaves.



Capacity

STATIM G4 autoclaves not only offer fast sterilization times but also enough capacity to meet the needs of a busy practice.

STATIM 2000 G4 capacity allows for up to 5 pouches and the STATIM 5000 G4 allows for up to 10 pouches.



G4 Technology

SciCan's G4 equipment can connect and send information to your smart devices so you can have cycle data, instructions, and maintenance notifications at your fingertips.



Gentle

The fresh water feature guarantees fresh water with every cycle. State-of-the-art steam technology is gentle on both solid and hollow instruments.



 COLTENE

STAT/M 2000 G4 Specifications

p/n G4-121106

Unit size (L x W x H):

19.5" x 16.25" x 6" / 49.5 cm x 41.5 cm x 15 cm

Cassette internal dimensions:

11" x 7" x 1.4" / 28 cm x 18 cm x 3.5 cm

Minimum shelf height for proper leveling:

8.5" / 22 cm

Weight without water:

46 lbs / 21 kg

Power consumption:

115 V, 60 Hz, 11A

	Unwrapped	Wrapped	Rubber / Plastic	Air Drying
Sterilization Time	3.5 minutes	10 minutes	15 minutes	Air drying only
Sterilization Temp	135° C	135° C	121° C	Air drying only
Total Cycle Time*	6 minutes	14 minutes	20 minutes	Air drying only

*Cycle time is dependent on instrument load and does not include drying.

STAT/M 5000 G4 Specifications

p/n G4-201102

Unit size (L x W x H):

23.6" x 16.1" x 7.5" / 60 cm x 41 cm x 19 cm

Cassette internal dimensions:

15" x 7" x 3" / 38 cm x 18 cm x 7.5 cm

Minimum shelf height for proper leveling:

10" / 26 cm

Weight without water:

73 lbs / 33 kg

Power consumption:

115 V, 60 Hz, 11A

	Unwrapped	Wrapped	Rubber / Plastic	Heavy Duty Unwrapped
Sterilization Time	3.5 minutes	6 minutes	15 minutes	6 minutes
Sterilization Temp	134° C	134° C	121° C	134° C
Total Cycle Time*	9 minutes	17.5 minutes	24 minutes	12 minutes

*Cycle time is dependent on instrument load and does not include drying.



VistaPure™

Water Filtration

Provides two grades of high-quality water for autoclaves, dental bottles, ultrasonic cleaners and the rinse cycle of instrument washers.

V3000



STATMAT™

Protect your STAT/M

Securely seat cassettes atop your STAT/M with a safe and hygienic silicone mat.

01-112867S - For STAT/M 2000

01-112868S - For STAT/M 5000



VistaPure™ AutoFill

Replenish any new or older-model STAT/M and BRAVO autoclave with distilled-quality water automatically, enabling truly hands-free convenience.

S3020 - AutoFill for STAT/M

S3030 - AutoFill for BRAVO



STAT-DRI™ Plus

Drying Agent

Enhance drying in your STAT/M Cassettes with the STAT-DRI Plus drying agents.

2OZPLUS - Stat-Dri Plus 2 oz with Sprayer

8OZPLUST - Stat-Dri Plus 8 oz with Sprayer

8OZPLUS - Stat-Dri Plus 8 oz with Cap (refill)

32OZPLUS - Stat-Dri Plus 32 oz with Cap (refill)

T473 - Spray Trigger Only for 32 oz Bottle



VistaCool™

Direct-to-Drain System

Protects cabinets and drains—and saves valuable staff time—by cooling autoclave wastewater and sending it directly down the drain automatically.

V7501 - For One Autoclave

V7502 - For Two Autoclaves

Manufactured by:
SciCan Ltd.
1440 Don Mills Rd.,
Toronto, ON, Canada, M3B 3P9
Tel: 416-445-1600
Toll free: 1-800-667-7733
customerservice@scican.com

VistaPure™, VistaPure AutoFill and VistaCool™
are manufactured by:
Vista Research Group
PO Box 321, Ashland, Ohio 44805-0321 USA
Tel: (419) 285-3927
VistaResearchGroup.com

www.scican.com

COLTENE

STAT/M is a registered trademark and STAT-DRI and STATMAT are trademarks of SciCan Ltd. VistaCool, VistaPure and DrainHub are trademarks of Vista Research Group.

SD-540 CA EN R2