

# SciCan STATIM® G4

Cassette Autoclaves



## STERILIZATION AND DRYNESS

at speeds faster than conventional chambered autoclaves



### Fast Cycle Times

STATIM 2000 G4 unwrapped cycle times are the world's fastest at 6 minutes. Wrapped cycles, including drying, can be completed in as little as 35 minutes.

STATIM 5000 G4 can complete unwrapped cycles in as little as 9 minutes. Wrapped cycles, including drying, can be completed in as little as 40 minutes.



### Reliable

For over 25 years, STATIM's unmatched speed, reliability, and dependability have made it one of the world's best selling cassette autoclaves.



### Capacity

STATIM G4 autoclaves not only offer fast sterilization times but also enough capacity to meet the needs of a busy practice.

STATIM 2000 G4 capacity allows for up to 5 pouches and the STATIM 5000 G4 allows for up to 10 pouches.



### G4 Technology

SciCan's G4 equipment can connect and send information to your smart devices so you can have cycle data, instructions, and maintenance notifications at your fingertips.



### Gentle

The fresh water feature guarantees fresh water with every cycle. State-of-the-art steam technology is gentle on both solid and hollow instruments.



## STAT/M 2000 G4 Specifications

p/n G4-121106

### Unit size (L x W x H):

19.5" x 16.25" x 6" / 49.5 cm x 41.5 cm x 15 cm

### Cassette internal dimensions:

11" x 7" x 1.4" / 28 cm x 18 cm x 3.5 cm

### Minimum shelf height for proper leveling:

8.5" / 22 cm

### Weight without water:

46 lbs / 21 kg

### Power consumption:

115 V, 60 Hz, 11A

	Unwrapped	Wrapped	Rubber / Plastic	Air Drying
<b>Sterilization Time</b>	3.5 minutes	10 minutes	15 minutes	Air drying only
<b>Sterilization Temp</b>	135° C	135° C	121° C	Air drying only
<b>Total Cycle Time*</b>	6 minutes	14 minutes	20 minutes	Air drying only

\*Cycle time is dependent on instrument load and does not include drying.

## STAT/M 5000 G4 Specifications

p/n G4-201102

### Unit size (L x W x H):

23.6" x 16.1" x 7.5" / 60 cm x 41 cm x 19 cm

### Cassette internal dimensions:

15" x 7" x 3" / 38 cm x 18 cm x 7.5 cm

### Minimum shelf height for proper leveling:

10" / 26 cm

### Weight without water:


73 lbs / 33 kg

### Power consumption:

115 V, 60 Hz, 11A

	Unwrapped	Wrapped	Rubber / Plastic	Heavy Duty Unwrapped
<b>Sterilization Time</b>	3.5 minutes	6 minutes	15 minutes	6 minutes
<b>Sterilization Temp</b>	134° C	134° C	121° C	134° C
<b>Total Cycle Time*</b>	9 minutes	17.5 minutes	24 minutes	12 minutes

\*Cycle time is dependent on instrument load and does not include drying.



## VistaPure™

### Water Filtration

Provides two grades of high-quality water for autoclaves, dental bottles, ultrasonic cleaners and the rinse cycle of instrument washers.

V3000



## STATMAT™

### Protect your STAT/M

Securely seat cassettes atop your STAT/M with a safe and hygienic silicone mat.

01-112867S - For STAT/M 2000

01-112868S - For STAT/M 5000



## VistaPure™ AutoFill

Replenish any new or older-model STAT/M and BRAVO autoclave with distilled-quality water automatically, enabling truly hands-free convenience.

S3020 - AutoFill for STAT/M

S3030 - AutoFill for BRAVO



## STAT-DRI™ Plus

### Drying Agent

Enhance drying in your STAT/M Cassettes with the STAT-DRI Plus drying agents.

2OZPLUS - Stat-Dri Plus 2 oz with Sprayer

8OZPLUST - Stat-Dri Plus 8 oz with Sprayer

8OZPLUS - Stat-Dri Plus 8 oz with Cap (refill)

32OZPLUS - Stat-Dri Plus 32 oz with Cap (refill)

T473 - Spray Trigger Only for 32 oz Bottle



## VistaCool™

### Direct-to-Drain System

Protects cabinets and drains—and saves valuable staff time—by cooling autoclave wastewater and sending it directly down the drain automatically.

V7501 - For One Autoclave

V7502 - For Two Autoclaves

Manufactured by:

**SciCan Ltd.**

1440 Don Mills Rd.,  
Toronto, ON, Canada, M3B 3P9  
Tel: 416-445-1600  
Toll free: 1-800-667-7733  
customerservice@scican.com

VistaPure™, VistaPure AutoFill and VistaCool™  
are manufactured by:

**Vista Research Group**

PO Box 321, Ashland, Ohio 44805-0321 USA  
Tel: (419) 285-3927  
VistaResearchGroup.com

[www.scican.com](http://www.scican.com)

**COLTENE**

SD-540 CA EN R2